

Unique Features

Water penetration resistance

Mobility Zone

Invacare Softform Premier Active 2





35 kPa minimum (BS 3424: part 26). 35 kPa minimum after 20,000 cycles

Martindale Abrasion Test EN ISO 5470-2

| Air Insert contained within standard Softform Premier mattress foam construction | Using the pump allows stepping up and down between Reactive and Active alternating systems with minimum patient disruption | | | | |
|---|--|--|--|--|--|
| Inflation of air cells alternates on a 10 minute cycle | Promotes tissue recovery and pressure distribution | | | | |
| New air cell design | For the users safety and peace of mind | | | | |
| Air system placed beneath foam insert | Greatly reduces risk of sharps puncture | | | | |
| Mattress can stay on the bed for a wide range of patients. | Reduces moving and handling issues; minimizes additional storage requirements. | | | | |
| High risk static mattress, delivering exceptional pressure reduction and patient comfort | In the event of a power failure, the patient is still resting on a high risk pressure reducing surface, minimizing the potential of pressure damage occurring until power is restored | | | | |
| Mattress does not require turning | Reduces manual handling issues | | | | |
| Two-way stretch PU waterproof cover | Provides excellent recovery and durability, and helps reduce shear and friction forces | | | | |
| High frequency welded seams | Reduces the risk of fluid ingress | | | | |
| Full length flap conceals the zlp | Reduces the possible fluid ingress through the zip | | | | |
| Toughened PU coated base | Prolongs the longevity of the mattress | | | | |
| Single piece of foam "U" core | Facilitates patient transfer by providing side wall support | | | | |
| | factorial and the second secon | | | | |

Benefits

| CODE | DESCRIPTION | TOTAL LENGTH | TOTAL WIDTH | TOTAL HEIGHT | SWL | UNIT WEIGHT |
|-------------|---------------------------------------|-----------------|----------------|-----------------|---------|----------------|
| SPAM2197/88 | Invacare Softform Premier Active 2 | 1970mm | 880mm | 152mm | 247.6KG | 14 Kg |